

# **FERM<sup>®</sup>**

## **INDUSTRIAL**



**DEVELOPED IN THE NETHERLANDS**

***CATALOG***

# ***FERM INDUSTRIAL***

## ***AFFORDABLE INDUSTRIAL POWER TOOLS***

Since the company began in 1965 in Zwolle, The Netherlands, FERM grew to be one of the leading power tool brands in Europe. FERM strives to ensure 100% confidence and satisfaction to its customers worldwide, by offering durable and high-performance Industrial power tools, for an affordable price.

With a renewed focus, FERM invested time to work side-by-side with real users of professional tools to understand their specific demands at the jobsite. Especially for craftsmen, construction workers, tradesmen and other professionals who require professional power tools for an affordable price, FERM designed, developed and produced its FERM INDUSTRIAL power tool assortment.

FERM INDUSTRIAL power tools consists of a wide range of affordable high quality power tools and accessories for the professional market. FERM also offers competitively priced spare parts and excellent serviceability of our power tools. All FERM Industrial products are developed, produced and tested according to the strict European standards and our company is known for its quality products and excellent service.

Rick Rosberg  
CEO



## ANGLE GRINDER

### 850W - 100MM AGM1111P

#### Specifications

|                |                    |
|----------------|--------------------|
| Mains voltage  | 220-240V~, 50/60Hz |
| Power input    | 850W               |
| Disc diameter  | 100mm              |
| No load speed  | 11.000/min.        |
| Spindle        | M10                |
| Machine weight | 1.98kg             |

#### Features

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench

## ANGLE GRINDER

### 710W - 115MM AGM1112P

#### Specifications

|                |                    |
|----------------|--------------------|
| Mains voltage  | 220-240V~, 50/60Hz |
| Power input    | 710W               |
| Disc diameter  | 115mm              |
| No load speed  | 11.000/min.        |
| Spindle        | M14                |
| Machine weight | 2.00kg             |

#### Features

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench

## ANGLE GRINDER

### 850W - 115MM AGM1113P

#### Specifications

|                |                    |
|----------------|--------------------|
| Mains voltage  | 220-240V~, 50/60Hz |
| Power input    | 850W               |
| Disc diameter  | 115mm              |
| No load speed  | 11.000/min.        |
| Spindle        | M14                |
| Machine weight | 2.00kg             |

#### Features

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench

## ANGLE GRINDER

### 950W - 125MM AGM1095P

#### Specifications

|                |                 |
|----------------|-----------------|
| Mains voltage  | 230-240V~, 50Hz |
| Power input    | 950W            |
| Disc diameter  | 125mm           |
| No load speed  | 12.000/min.     |
| Spindle        | M14             |
| Machine weight | 2.10kg          |

#### Features

- Electronic restart protection
- Lock-on switch
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench

## ANGLE GRINDER

### 2300W - 180MM AGM1116P

#### Specifications

|                |                    |
|----------------|--------------------|
| Mains voltage  | 220-240V~, 50/60Hz |
| Power input    | 2.300W             |
| Disc diameter  | 180mm              |
| No load speed  | 8.500/min.         |
| Spindle        | M14                |
| Machine weight | 6.00kg             |

#### Features

- Lock-off safety switch
- Soft start
- Spindle lock
- Adjustable rear handle
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench - Hex key

## ANGLE GRINDER

### 2600W - 230MM AGM1119P

#### Specifications

|                |                    |
|----------------|--------------------|
| Mains voltage  | 220-240V~, 50/60Hz |
| Power input    | 2.600W             |
| Disc diameter  | 230mm              |
| No load speed  | 6.500/min.         |
| Spindle        | M14                |
| Machine weight | 6.70kg             |

#### Features

- Lock-off safety switch
- Soft start
- Spindle lock
- Adjustable open safety guard
- 3m rubber cable



Includes Side handle - Wrench - Hex key

## CHOP SAW 2300W - 355MM COM1007P

### Specifications

|                |                 |
|----------------|-----------------|
| Mains voltage  | 220-240V~, 50Hz |
| Power input    | 2.300W          |
| Disc diameter  | 355mm           |
| No load speed  | 4.000/min.      |
| Spindle        | Ø1 inch         |
| Machine weight | 15.80kg         |

### Features

- Heavy duty base
- Spindle lock
- Quick lock vise
- Adjustable depth stop
- High cutting capacity
- 4m rubber cable



Includes Wrench - Cutting blade  
Optional accessories COA1005 Cutting disc 355x2.8x25.4mm Inox/ stainless steel

## CIRCULAR SAW 2200W - 235MM CSM1042P

### Specifications

|                    |                 |
|--------------------|-----------------|
| Mains voltage      | 220-240V~, 50Hz |
| Power input        | 2.200W          |
| No load speed      | 3.900/min.      |
| Saw blade diameter | Ø235mm          |
| Saw blade bore     | Ø30mm           |
| Bevel adjustment   | 0-45°           |
| Machine weight     | 7.00kg          |

### Features

- Angle and depth adjustment
- Spindle lock
- Lock-off safety switch
- High quality blade included
- 3m rubber cable



Includes Saw blade 235mm - Hexagon key - Parallel guide

## JIG SAW 450W JSM1028P

### Specifications

|                  |                 |
|------------------|-----------------|
| Mains voltage    | 220-240V~, 50Hz |
| Power input      | 450W            |
| No load speed    | 0-3.400/min.    |
| Bevel adjustment | 0-45°           |
| Machine weight   | 2.10kg          |

### Features

- Variable electronic speed control
- 4 pendulum positions
- Variable angle adjustment (0-45°)
- 3m rubber cable
- Storage case



Includes Saw blade wood - Saw blade steel

## JIG SAW 750W JSM1025P

### Specifications

|                  |                 |
|------------------|-----------------|
| Mains voltage    | 230-240V~, 50Hz |
| Power input      | 750W            |
| No load speed    | 500-3.000/min.  |
| Bevel adjustment | 0-45°           |
| Machine weight   | 3.30kg          |

### Features

- Variable electronic speed control
- Toolless saw blade release
- 4 pendulum positions
- Variable angle adjustment (0-45°)
- 4m rubber cable
- Storage case



Includes Saw blade wood - Splinter plate - Vacuum cleaner adapter - Anti-scratch plate - Parallel guide

## WALL CHASER 2400W - 150MM WCM1001P

### Specifications

|                |             |
|----------------|-------------|
| Mains voltage  | 230V~, 50Hz |
| Power input    | 2.400W      |
| Disc diameter  | 150mm       |
| No load speed  | 8.000/min.  |
| Spindle        | 22.2mm      |
| Cutting depth  | 0-43mm      |
| Cutting width  | 30mm        |
| Machine weight | 6.10kg      |

### Features

- Efficient wall chasing without chiselling due to 3-in-1 blades
- Toolless adjustment of cutting depth
- Convenient switch with lock-on for continuous operation
- Dust extraction system
- Metal support rollers
- Spindle lock
- Storage case
- 4m rubber cable



Includes Spanners - 3-in-1 blade  
Optional accessories WCA1001 Wall chaser blade 3-in-1 (150x22.2mm)





## ELECTRIC DRILL

### 450W - 10MM PDM1048P

#### Specifications

|                |                 |
|----------------|-----------------|
| Mains voltage  | 220-240V~, 50Hz |
| Power input    | 450W            |
| No load speed  | 0-3.300/min.    |
| Chuck capacity | Ø1.5-10mm       |
| Machine weight | 1.50kg          |

#### Features

- Single function (drilling)
- Left/right rotation
- Variable electronic speed control
- 3m rubber cable



Includes Chuck key

## IMPACT DRILL

### 710W - 13MM PDM1049P\_K

#### Specifications

|                |                 |
|----------------|-----------------|
| Mains voltage  | 220-240V~, 50Hz |
| Power input    | 710W            |
| No load speed  | 0-3.200/min.    |
| Impact rate    | 0-51.200/min.   |
| Chuck capacity | Ø1.5-13mm       |
| Machine weight | 2.00kg          |

#### Features

- Keyless metal chuck
- Double function (drilling and impact drilling)
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable



Includes Auxiliary handle - Metal depth limiter

## IMPACT DRILL

### 710W - 13MM PDM1050P

#### Specifications

|                |                 |
|----------------|-----------------|
| Mains voltage  | 220-240V~, 50Hz |
| Power input    | 710W            |
| No load speed  | 0-3.200/min.    |
| Impact rate    | 0-51.200/min.   |
| Chuck capacity | Ø1.5-13mm       |
| Machine weight | 2.20kg          |

#### Features

- Double function (drilling and impact drilling)
- Metal gear housing
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable



Includes Auxiliary handle - Metal depth limiter

## IMPACT DRILL

### 850W - 13MM PDM1060P\_K

#### Specifications

|                |                    |
|----------------|--------------------|
| Mains voltage  | 220-240V~, 50/60Hz |
| Power input    | 850W               |
| No load speed  | 0-3.000/min.       |
| Impact rate    | 0-48.000/min.      |
| Chuck capacity | Ø1.5-13mm          |
| Machine weight | 2.08kg             |

#### Features

- Keyless metal chuck
- Double function (drilling and impact drilling)
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable
- Storage case



Includes Auxiliary handle - Metal depth limiter

## IMPACT DRILL

### 1100W - 13MM PDM1061P\_K

#### Specifications

|                   |                    |
|-------------------|--------------------|
| Mains voltage     | 220-240V~, 50/60Hz |
| Power input       | 1.100W             |
| Mechanical speeds | 2                  |
| No load speed     | 0-1.200/min.       |
|                   | 0-3.100/min.       |
| Impact rate       | 0-19.200/min.      |
|                   | 0-49.600/min.      |
| Chuck capacity    | Ø1.5-13mm          |
| Machine weight    | 3.28kg             |

#### Features

- Keyless metal chuck
- Double function (drilling and impact drilling)
- Mechanical 2 speed gearbox
- Metal gear housing
- Variable electronic speed control
- Side handle with metal depth limiter
- 3m rubber cable
- Storage case



Includes Auxiliary handle - Metal depth limiter



## ROTARY HAMMER

### 800W - 3.3KG HDM1038P

#### Specifications

|                |                 |
|----------------|-----------------|
| Mains voltage  | 220-240V~, 50Hz |
| Power input    | 800W            |
| No load speed  | 0-1.250/min.    |
| Impact rate    | 0-5.500/min.    |
| Chuck size     | SDS-plus        |
| Impact energy  | 2.7 Joule       |
| Machine weight | 3.30kg          |



#### Features

- 4 Functions (drilling, hammer drilling, chiseling, free rotation chiseling)
- Universal SDS-plus chuck
- Variable electronic speed control
- 3m rubber cable
- Storage case

Includes Auxiliary handle - Metal depth limiter - 3 SDS concrete drills - Chisel pointed - Chisel flat

## ROTARY HAMMER

### 1100W - 6.6KG HDM1043P

#### Specifications

|                   |                  |
|-------------------|------------------|
| Mains voltage     | 220-240V~, 50Hz  |
| Power input       | 1.100W           |
| No load speed     | 300-760/min.     |
| Impact rate       | 1.950-4.860/min. |
| Chuck size        | SDS-max          |
| Impact energy     | 1-7 Joule        |
| Machine weight    | 6.60kg           |
| Drilling capacity | 35mm             |



#### Features

- 3 Functions (hammer drilling, chiseling, free rotation chiseling)
- SDS-max chuck
- Soft start
- Variable electronic speed control
- Vibration reduction rear handle
- 5m rubber cable
- Storage case

Includes Auxiliary handle - Depth limiter

## DEMOLITION HAMMER

### 1200W - 6.2KG HDM1040P

#### Specifications

|                |                 |
|----------------|-----------------|
| Mains voltage  | 220-240V~, 50Hz |
| Power input    | 1.200W          |
| Impact rate    | 3.100/min.      |
| Chuck size     | SDS-max         |
| Impact energy  | 14 Joule        |
| Machine weight | 6.20kg          |



#### Features

- Single function (chiselling)
- SDS-max chuck
- Powerful lightweight machine (14 joule - 6.2kg)
- 12 step adjustable chisel position
- Vibration reduction rear handle
- 5m rubber cable
- Storage case

Includes Auxiliary handle - Chisel pointed - Chisel flat

## DEMOLITION HAMMER

### 1500W - 11KG HDM1041P

#### Specifications

|                |                  |
|----------------|------------------|
| Mains voltage  | 220-240V~, 50Hz  |
| Power input    | 1.500W           |
| Impact rate    | 1.000-1.900/min. |
| Chuck size     | SDS-max          |
| Impact energy  | 6-25 Joule       |
| Machine weight | 11.00kg          |



#### Features

- Single function (chiselling)
- SDS-max chuck
- Powerful heavy duty machine (6 - 25 joule - 11.0kg)
- 12 step adjustable chisel position
- Vibration reduction rear handle
- 5m rubber cable
- Storage case

Includes Auxiliary handle - Chisel pointed - Chisel flat

## DEMOLITION HAMMER

### 1500W - 16KG HDM1042P

#### Specifications

|                |             |
|----------------|-------------|
| Mains voltage  | 230V~, 50Hz |
| Power input    | 1.500W      |
| Impact rate    | 1.400/min.  |
| Chuck size     | Hex 30mm    |
| Impact energy  | 50 Joule    |
| Machine weight | 16.00kg     |



#### Features

- Single function (chiselling)
- Hex 30mm chuck
- Powerful heavy duty machine (50 joule - 16kg)
- Vibration reduction rear handle
- 5m rubber cable
- Storage case (with transport wheels)

Includes Auxiliary handle - Chisel pointed - Chisel flat



## HOT AIR GUN 2000W HAM1017P

### Specifications

|                            |                 |
|----------------------------|-----------------|
| Mains voltage              | 220-240V~, 50Hz |
| Power input                | 2.000W          |
| Temperature setting        | Variable        |
| Temp/air volume setting 1: | 50°C            |
|                            | (250L/min.)     |
| Temp/air volume setting 2: | 50°-450°C       |
|                            | (250L/min.)     |
| Temp/air volume setting 3: | 90°-600°C       |
|                            | (500L/min.)     |
| Machine weight             | 0.90kg          |

### Features

- Over heating protection
- Ceramic heating elements
- 3 Air speed setting
- Constant temperature control, adjustable by dial wheel
- 3m rubber cable



## ANGLE POLISHER 1400W - 180MM AGM1120P

### Specifications

|                |                  |
|----------------|------------------|
| Mains voltage  | 220-240V~, 50Hz  |
| Power input    | 1.400W           |
| Disc diameter  | 180mm            |
| No load speed  | 1.000-3.300/min. |
| Spindle        | M14              |
| Machine weight | 3.10kg           |

### Features

- Variable electronic speed control
- Constant speed electronics
- Spindle lock
- 4m rubber cable



Includes Front handle - Hexagon key - Base plate (Velcro®) - Polishing foam pad - Polishing wool pad - Nylon accessory bag

## ELECTRIC DUST BLOWER 600W EBM1004P

### Specifications

|                 |                 |
|-----------------|-----------------|
| Mains voltage   | 220-240V~, 50Hz |
| Power input     | 600W            |
| Nozzel diameter | 30mm            |
| No load speed   | 0-13.900/min.   |
| Air volume      | 0-4.1 m³/min    |
| Machine weight  | 2.30kg          |

### Features

- Variable electronic air speed control
- Lock-on switch
- Blower and vacuum function
- Long blow pipe with extension (total lenght 52cm)
- 3m rubber cable



Includes Blow pipe - Blow pipe extension piece - Dust bag





## CORDLESS LI-ION DRILL 20V - 2.0AH CDM1141P

**FI20V**

### Specifications

|                           |                               |
|---------------------------|-------------------------------|
| Charger voltage           | 230-240V~, 50Hz               |
| Voltage                   | 20V Li-Ion (2.0Ah)            |
| No load speed position I  | 0-450/min.                    |
| No load speed position II | 0-1.700/min.                  |
| Chuck capacity            | Ø1.5-13mm                     |
| Torque positions          | 21+1                          |
| Max. torque (hard)        | 50Nm                          |
| Machine weight            | 1.24kg (without battery pack) |



### Features

- 4-pole Mabuchi® motor
- Metal Jacobs® chuck
- Samsung® 2.0 Ah battery cells
- 60 min. quick charger
- Variable electronic speed control
- LED light
- Storage case

|                      |  |
|----------------------|--|
| Includes             | 2 Li-Ion 2.0 Ah batteries - 2 screwdriver bits - quick charger |
| Optional accessories | Battery CDA1132P, CDA1133P                                     |
| Optional accessories | Charger CDA1131P, CDA1147P                                     |



## BATTERY 20V - 2.0AH CDA1132P

**FI20V**

### Specifications

|                |                         |
|----------------|-------------------------|
| Voltage        | 20V                     |
| Ampere hour    | 2.0Ah                   |
| Battery type   | Li-Ion                  |
| Charging time  | 45 min. (With CDA1147P) |
| Charging time  | 60 min. (With CDA1131P) |
| Battery weight | 0.38 kg                 |



### Features

- Samsung® battery cells
- Battery charge indication
- Softgrip

## BATTERY 20V - 4.0AH CDA1133P

**FI20V**

### Specifications

|                |                         |
|----------------|-------------------------|
| Voltage        | 20V                     |
| Ampere hour    | 4.0Ah                   |
| Battery type   | Li-Ion                  |
| Charging time  | 60 min. (With CDA1147P) |
| Charging time  | 90 min. (With CDA1131P) |
| Battery weight | 0.65 kg                 |



### Features

- Samsung® battery cells
- Battery charge indication
- Softgrip

## QUICK CHARGER 20V - 2.0A CDA1131P

**FI20V**

### Specifications

|                |                          |
|----------------|--------------------------|
| Charger input  | 100-240V<br>50/60Hz, 50W |
| Charger output | 20V 2A                   |
| Charger weight | 0.36 kg                  |



### Features

- Charge indication
- Charging time with CDA1132P  
60 minutes
- Charging time with CDA1133P  
90 minutes

|                      |                            |
|----------------------|----------------------------|
| Optional Accessories | Battery CDA1132P, CDA1133P |
|----------------------|----------------------------|

## QUICK CHARGER 20V - 4.0A CDA1147P

**FI20V**

### Specifications

|                |                          |
|----------------|--------------------------|
| Charger input  | 100-240V<br>50/60Hz, 98W |
| Charger output | 20V 4A                   |
| Charger weight | 0.53 kg                  |



### Features

- Charge indication
- Charging time with CDA1132P  
45 minutes
- Charging time with CDA1133P  
60 minutes

|                      |                            |
|----------------------|----------------------------|
| Optional Accessories | Battery CDA1132P, CDA1133P |
|----------------------|----------------------------|





**WWW.FERM-INDUSTRIAL.COM**

**BERNER OF KUWAIT W.L.L.  
CREATIVE DESIGN CENTER  
SHUWAIKH INDUSTRIAL AREA**

**KUWAIT**

**P. O. BOX 42211 SHUWAIKH INDUSTRIAL 70653  
T: +965 22263502  
F: +965 22263503**

**WELCOME@BERNER.COM.KW**